



Housing: Die cast aluminum, alloy A380 with baked blue enamel finish per FED-STD-595, color 25109

Cover: Aluminum alloy 1100-H14 with clear anodized per MIL-A-8625

Shape: 1 degree draft per side

MILESTEK PART NUMBER	TRANSFORMER RATIO T1-T8	R1-R16 STUB RESISTOR VALUE	R17 BUS RESISTOR VALUE	R18 BUS RESISTOR VALUE	BUS 1 CONNECTOR TRB 3-LUG	BUS 2 CONNECTOR TRB 3-LUG	STUB CONNECTOR TRB 3-LUG
90-50208	1.41:1	59 ohm, 2W, 1%	n/a	n/a	10-06592	10-06592	10-06592
90-50218	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	10-06592	10-06592
90-50538	1:1	59 ohm, 2W, 1%	n/a	n/a	10-06592	10-06592	10-06592
90-50548	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	10-06592	10-06592
90-50638	1:1	54.9 ohm, 2W, 1%	n/a	n/a	10-06592	10-06592	10-06592
90-50648	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	10-06592	10-06592
90-51218	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-51548	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-51648	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-52218	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-52548	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-52648	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-50228	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	n/a	10-06592
90-50558	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	n/a	10-06592
90-50658	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	n/a	10-06592

Milestek®

MILESTEK CORPORATION
1506 INTERSTATE 35 WEST
DENTON, TX 76207
TELEPHONE: 940.484.9400
TOLL FREE: 866.524.1553
FAX: 940.591.7086

Please visit www.milestek1553.com for additional information.

Drawn by: Mark Hearn	Approved by: Robert Perez	Date: 11/8/04
Title: 8 Stub Couplers	Cage Code: 4Z977	
Drawing Number: 9058	ISO 9001:2000 CERTIFIED	Rev:
Scale: Not to scale	Tolerance: <.1 +/- .01 / >.1 +/- .1	Sheet: 1 of 1