



**Housing:** Die cast aluminum, alloy A380 with baked blue enamel finish per FED-STD-595, color 25109

**Cover:** Aluminum alloy 1100-H14 with clear anodized per MIL-A-8625

**Shape:** 1 degree draft per side

MILESTEK PART NUMBER	TRANSFORMER RATIO T1	R1-R2 STUB RESISTOR VALUE	R3 BUS RESISTOR VALUE	R4 BUS RESISTOR VALUE	BUS 1 CONNECTOR TRB 3-LUG	BUS 2 CONNECTOR TRB 3-LUG	STUB CONNECTOR TRB 3-LUG
90-50201	1.41:1	59 ohm, 2W, 1%	n/a	n/a	10-06592	10-06592	10-06592
90-50211	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	10-06592	10-06592
90-50531	1:1	59 ohm, 2W, 1%	n/a	n/a	10-06592	10-06592	10-06592
90-50541	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	10-06592	10-06592
90-50631	1:1	54.9 ohm, 2W, 1%	n/a	n/a	10-06592	10-06592	10-06592
90-50641	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	10-06592	10-06592
90-51211	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-51541	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-51641	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-52211	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-52541	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-52641	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-50221	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	n/a	10-06592
90-50551	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	n/a	10-06592
90-50651	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	n/a	10-06592

**Milestek®**

MILESTEK CORPORATION  
1506 INTERSTATE 35 WEST  
DENTON, TX 76207  
TELEPHONE: 940.484.9400  
TOLL FREE: 866.524.1553  
FAX: 940.591.7086

Please visit [www.milestek1553.com](http://www.milestek1553.com) for additional information.

Drawn by: Mark Hearn	Approved by: Robert Perez	Date: 11/4/04
Title: 1 Stub Couplers	Cage Code: 4Z977	
Drawing Number: 9051	ISO 9001:2000 CERTIFIED	Rev:
Scale: Not to scale	Tolerance: <.1 +/- .01 / >.1 +/- .1	Sheet: 1 of 1