



Housing: Die cast aluminum, alloy A380 with baked blue enamel finish per FED-STD-595, color 25109

Cover: Aluminum alloy 1100-H14 with clear anodized per MIL-A-8625

Shape: 1 degree draft per side

MILESTEK PART NUMBER	TRANSFORMER RATIO T1-T2	R1-R4 STUB RESISTOR VALUE	R5 BUS RESISTOR VALUE	R6 BUS RESISTOR VALUE	BUS 1 CONNECTOR TRB 3-LUG	BUS 2 CONNECTOR TRB 3-LUG	STUB CONNECTOR TRB 3-LUG
90-50202	1.41:1	59 ohm, 2W, 1%	n/a	n/a	10-06592	10-06592	10-06592
90-50212	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	10-06592	10-06592
90-50532	1:1	59 ohm, 2W, 1%	n/a	n/a	10-06592	10-06592	10-06592
90-50542	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	10-06592	10-06592
90-50632	1:1	54.9 ohm, 2W, 1%	n/a	n/a	10-06592	10-06592	10-06592
90-50642	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	10-06592	10-06592
90-51212	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-51542	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-51642	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-52212	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-52542	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-52642	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	10-06592	n/a	10-06592
90-50222	1.41:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	n/a	10-06592
90-50552	1:1	59 ohm, 2W, 1%	78.7 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	n/a	10-06592
90-50652	1:1	54.9 ohm, 2W, 1%	78.7 ohm, 2W, 1%	78.7 ohm, 2W, 1%	n/a	n/a	10-06592

Milestek®
 MILESTEK CORPORATION
 1506 INTERSTATE 35 WEST
 DENTON, TX 76207
 TELEPHONE: 940.484.9400
 TOLL FREE: 866.524.1553
 FAX: 940.591.7086

Please visit www.milestek1553.com for additional information.

Drawn by: Mark Hearn	Approved by: Robert Perez	Date: 11/5/04
Title: 2 Stub Couplers	Cage Code: 4Z977	
Drawing Number: 9052	ISO 9001:2000 CERTIFIED	Rev:
Scale: Not to scale	Tolerance: <.1 +/- .01 / >.1 +/- .1	Sheet: 1 of 1